



RC11/12

TECHNICAL SPECIFICATION						
CABLE TYPE		RG-59BU COAXIAL CABEL				
STRUCTURE						
Conductor	Composition(No./mm)	1/0.584mm				
	Material	Copper Covered Steel Wire				
	Outside Diameter (mm)	0.584±0.02mm				
Insulation	Material	Solid Polyethylene				
	Thickness (mm)	1.56mm				
	Nom. Diameter(mm)	3.71± 0.10mm				
Shield	Material	Bare Copper Wire				
	Construction	16x7/0.12mm				
	Coverage	90%				
	Diameter(mm)	0.12±0.008mm				
Jacket	Material	PVC				
	Diameter(mm)	6.0 ± 0.10mm				
	Color	Black				
Printing	RG59B/U COAXIAL CABLE					
ELECTRICAL CHARACTERISTIC						
Impedance	Ω	75 ± 3				
Insulation Resistance	MΩ / km	1000 ↑				
Capacitance	pF/M	67 ± 3				
Attenuation	Frequency(MHz)	100	200	400	700	900
	dB/100M	11.2	16.1	23.2	31.8	36.5
<i>Nice Fountain Industrial Co., Ltd.</i>						
		DRWN.	Vivien Cheng			DRWN. No.:
		CHKD.	K.Y. WEI			
		APPD.	Vincent Shen			Date: July 20, 2001