



NOTE:
1) PRIMARY DIM:A
2) DIE NO:OU08003.

3	OUTER JACKET PVC 45Pa (ROHS)
2	RJ45 8P8C PLUG GOLD 50U" FOR UTP (ROHS)
1	CAT.6A UTP CABLE 24#4P STRANDED TYPE OD:6.0MM W/"+" XXMM (ROHS)

A	FIRST EDITION	05/01/06																
REV.	ECR	DESCRIPTION																
<small>THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF WIRETEK COMPUTER LIMITED AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF WIRETEK COMPUTER LIMITED.</small>		DATE																
<small>UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°</small>		TITLE																
<table border="1"> <tr> <th>DIMENSIONS</th> <th>TOLERANCE</th> </tr> <tr> <td>0.00 TO 30.00mm</td> <td>±0.10mm</td> </tr> <tr> <td>30.01 TO 80.00mm</td> <td>±0.13mm</td> </tr> <tr> <td>80.01 TO 150.00mm</td> <td>±0.15mm</td> </tr> <tr> <td>150.01mm</td> <td>±0.20mm</td> </tr> </table>		DIMENSIONS	TOLERANCE	0.00 TO 30.00mm	±0.10mm	30.01 TO 80.00mm	±0.13mm	80.01 TO 150.00mm	±0.15mm	150.01mm	±0.20mm	<table border="1"> <tr> <td colspan="2">UTP CABLE</td> </tr> <tr> <td>CHKD.</td> <td>CONF.</td> </tr> <tr> <td></td> <td>APPD.</td> </tr> </table>	UTP CABLE		CHKD.	CONF.		APPD.
DIMENSIONS	TOLERANCE																	
0.00 TO 30.00mm	±0.10mm																	
30.01 TO 80.00mm	±0.13mm																	
80.01 TO 150.00mm	±0.15mm																	
150.01mm	±0.20mm																	
UTP CABLE																		
CHKD.	CONF.																	
	APPD.																	
MATERIAL		SCALE / SHEET 1/1 UNIT MM SIZE A4 REV. A																
FINISH																		